



Thermocouple with bajonet fitting


Thermocouple	Fe-CuNi, NiCr-Ni other thermocouples on request
Operating temperature	500°C
Thermowell	Stainless steel
Nominal length	adjustable via spring with bajonet lock
Connection cable	Stranded Teflon insulated with glass fibre yarn cable filler and outside stainless steel wire standard length 2 m
Bajonet jacket	Complete stainless steel



D=G1/4"	1.36.04.01
D=G3/8"	1.36.04.02
D=M 14 x 1,5	1.36.04.03



1.36.04.04



1.36.04.05

Version		6mm Ø Tip flat			
L	Weight in kg	Order no. 1 x Fe-CuNi	Order no. 2 x Fe-CuNi	Order no. 1 x NiCr-Ni	Order no. 2 x NiCr-Ni
5	0,1	1.36.04.11	1.36.04.12	2.36.04.11	2.36.04.12
50	0,2	1.36.04.21	1.36.04.22	2.36.04.21	2.36.04.22

Version		6mm Ø Tip 120°C			
L	Weight in kg	Order no. 1 x Fe-CuNi	Order no. 2 x Fe-CuNi	Order no. 1 x NiCr-Ni	Order no. 2 x NiCr-Ni
5	0,1	1.36.04.31	1.36.04.32	2.26.04.31	2.36.04.32
50	0,2	1.36.04.41	1.36.04.42	2.36.04.41	2.36.04.42

Version		8mm Ø Tip flat			
L	Weight in kg	Order no. 1 x Fe-CuNi	Order no. 2 x Fe-CuNi	Order no. 1 x NiCr-Ni	Order no. 2 x NiCr-Ni
5	0,1	1.36.04.51	1.36.04.52	2.36.04.51	2.36.04.52
50	0,2	1.36.04.61	1.36.04.62	2.36.04.61	2.36.04.62

Version		8mm Ø Tip 120°flach			
L	Weight in kg	Order no. 1 x Fe-CuNi	Order no. 2 x Fe-CuNi	Order no. 1 x NiCr-Ni	Order no. 2 x NiCr-Ni
50	0,1	1.36.04.81	1.36.04.82	2.36.04.81	2.36.04.82
100	0,2	1.36.04.91	1.36.04.92	2.36.04.91	2.36.04.92
Addition	1 m Cable length		1.36.00.10		2.36.00.10

